

Mirafi® 180N





Mirafi[®] 180N is a needlepunched nonwoven geotextile composed of polypropylene fibers, which are formed into a stable network such that the fibers retain their relative position. Mirafi[®] 180N is inert to biological degradation and resists naturally encountered chemicals, alkalis, and acids. Mirafi[®] 180N meets AASHTO M288-06 Class 1 for Elongation > 50%.

TenCate Geosynthetics Americas Laboratories are accredited by <u>a2La</u> (The American Association for Laboratory Accreditation) and Geosynthetic Accreditation Institute – Laboratory Accreditation Program (<u>GAI-LAP</u>). <u>NTPEP Listed</u>

| Mechanical Properties | Test Method | Unit | Minimum Average Roll Value | | |
|------------------------------|-------------|------------------------|-------------------------------|------------|--|
| - | | | MD | CD | |
| Grab Tensile Strength | ASTM D4632 | lbs (N) | 205 (912) | 205 (912) | |
| Grab Tensile Elongation | ASTM D4632 | % | 50 | 50 | |
| Trapezoid Tear Strength | ASTM D4533 | lbs (N) | 80 (356) | 80 (356) | |
| CBR Puncture Strength | ASTM D6241 | lbs (N) | 500 (2224) | | |
| | | | Maximum Opening Size | | |
| Apparent Opening Size (AOS) | ASTM D4751 | U.S. Sieve (mm) | 80 (0.18) | | |
| | | | Minimum I | Roll Value | |
| Permittivity | ASTM D4491 | sec ⁻¹ | 1.4 | | |
| Flow Rate | ASTM D4491 | gal/min/ft2 (l/min/m2) | 95 (3870) | | |
| | | | Minimum Test Value | | |
| UV Resistance (at 500 hours) | ASTM D4355 | % strength retained | 70 |) | |

| Physical Properties | Unit | Roll Sizes | |
|----------------------------------|----------|------------------------|------------------------|
| Roll Dimensions (width x length) | ft (m) | 12.5 x 360 (3.8 x 110) | 15 x 300 (4.57 x 91.4) |
| Roll Area | yd² (m²) | 500 (418) | |

Disclaimer: TenCate assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Mirafi® is a registered trademark of Nicolon Corporation.

Copyright © 2015 Nicolon Corporation. All Rights Reserved.

365 South Holland Drive Pendergrass, GA 30567 Tel 706 693 2226 Tel 888 795 0808 Fax 706 693 4400 www.tencate.com





