

Sunray 480

- AllnGaP LED technology
- Environmentally friendly
- Cost effective
- Reliable and easy to operate
- Hundreds of pre-programmed messages, MUTCD messages, and operator-created messages
- Replace characters without the need of tools
- 5 LEDs per pixel, 15" letters
- Ergonomically designed control box



Display

Pixel Matrix SR480

Character size LEDs Brightness Photo Sensor Enclosure

Sign dimensions Characters Window 7 rows by 5 columns, 8 characters per line, 3 lines 15" fonts 590 nm amber, 5 per pixel, 30° Manual/automatic 31 levels Shielded from extraneous light Aluminum, finished powder coated black 59" high by 96" wide Removable without need for tools 1/8" clear polycarbonate anti-glare is optional

Control

Туре	Proprietary embedded fully NTCIP compliant
Dimming	Manual or automatic
LCD	4 lines, 40 characters
	per line, backlit
Remote Comm	Cellular capable
Messages	50 user programmable
	(4 pages each), 300
	pre-programmed
	including MUTCD
	symbols and arrows
Message scheduling	36 events

Trailer Construction

Width across fenders Drawbar

Fenders Frame Length w/ drawbar Length w/o drawbar Height sign up Height sign down Hitch Jacks Tire size Weight Lift Mechanism


78" 2 1/2" x 2 1/2" x .187" wall steel tube / removable formed steel replaceable 3" x 3" x 1/8" wall tubing 136" 106" 149" 104" 2" ball class II 3500 lb capacity (4) swing, (1) swing type w/ caster ST205/75-D15 load C 1600 lbs 2,500 lb with double disc brake. 1/4" diameter steel rope cable rated 4,400 lb. Electro-hydraulic optional


Batteries and Solar Collectors


Batteries	6v or 12v deep cycle with
	varying options
Battery Charger	15A to 30A fanned cooled,
	external plug, (45A optional)
Battery Enclosure	Lockable, ventilated, acid
	resistant
Solar Collector	Crystalline silicon, 85w

Options

- Combo hitch 2" ball & 3" pintle ring
- Speed detection
- Wheel locks
- Electro hydraulic lift
- Cellular phone for remote operation
- Color touch tablet
- •Hidden shackle lock brackets to secure batteries







Specifications subject to change any time without notice. Copyright 2017 National Signal, Inc. All rights reserved. Printed in the United States.



2440 Artesia Ave, Fullerton, CA 92833 fax: 714-441-7714 phone: 714-441-7707