

AMERDRAIN[®] 200 Sheet Drain **

PRODUCT DESCRIPTION

AMERDRAIN 200 sheet drain is a two-part prefabricated soil sheet drain consisting of a formed polystyrene core covered with a non-woven, needle-punched polypropylene filter fabric on the dimple side of the core. The fabric allows water to pass into the drain core. The core allows the water to flow to designated drainage exits.

BASIC USES


AMERDRAIN 200 sheet drain is designed primarily for vertical and horizontal applications at shallower depths where moderate compressive strength and flow capacity are adequate. The core side of AMERDRAIN 200 is placed against the wall surface of the foundation, or other similar structure. AMERDRAIN 200 provides full-coverage protection to waterproofing materials.

PACKAGING

- 4' x 50', 52' or 104' Rolls
- Available in different widths and lengths upon request.

COLLECTION SYSTEMS

AMERDRAIN 200 sheet drain can be used with AMERDRAIN TOTAL-DRAIN™ sheet drain for the collection and transportation of the water to designated exits.



INSTALLATION INSTRUCTIONS

DRAIN ATTACHMENT METHODS:

For attaching drain to waterproofing material, concrete or wood, several methods may be used including metal stick pins, nails driven through washers or wood lathing, construction adhesives or double sided tape. Discuss materials compatibility with waterproofing supplier before using adhesives. Typically any method used for attaching waterproofing protection board will work with drain. To attach drain to bare earth, use 4"- 8" anchor pins with washers.

VERTICAL:

AMERDRAIN 200 may be installed starting at the top or bottom of the wall. The roll may be installed either vertically (perpendicular to the footing) or horizontally (parallel to the footing). When installed vertically, the core flange should be at the upstream edge. This flange position minimizes seepage of water behind the drain similar to the way roof shingles work. When installed horizontally, the edge of the core with the flange should be at the top.

HORIZONTAL:

The edge of the core with the flange should be at the upstream side of the plaza.

CORNERS:

Bend AMERDRAIN 200 to make inside corners. For outside corners, cut drain core flush with corners leaving 3" of extra fabric. Wrap fabric around exposed edge of drain core, securing with tape to back side of core if necessary.

BACKFILLING:

Soil should be placed and compacted directly against the drain. Direct compactor exhaust away from drain to prevent damage. Backfill to a minimum 6" above drain to allow for coverage after settlement.

DETAILED INSTRUCTIONS FOR INSTALLATION AND TERMINATION ARE AVAILABLE UPON REQUEST.



AMERICAN WICK DRAIN CORPORATION

1209 Airport Road • Monroe, NC • 28110, USA
800 242-WICK • 704 238-9200 • Fax 704 296-0690
www.americanwick.com • info@americanwick.com

AMERDRAIN[®] 200 Sheet Drain **

Technical Data

PHYSICAL PROPERTIES	TYPICAL US VALUE	TYPICAL SI VALUE	TEST METHOD
FABRIC PROPERTIES			
Material	Polypropylene	Polypropylene	
Grab Tensile Strength	110 lbs	485N	ASTM D-4632
Puncture Strength	65 lbs	285N	ASTM D-4833
Trapezoidal Tear	50 lbs	220N	ASTM D-4533
Mullen Burst Strength	215 psi	1430 kPa	ASTM D-3786
Elongation	60%	60%	ASTM D-4632
EOS (AOS)	100 sieve	150 micron	ASTM D-4751
Permittivity	1.6 sec ⁻¹	1.6 sec ⁻¹	ASTM D-4491
Permeability	0.12 in/sec	0.3 cm/sec	ASTM D-4491
Flow Rate	150 gal/min/ft ²	6110 L/min/m ²	ASTM D-4491
UV Resistance (After 500 hrs.)	70%	70%	ASTM D-4355
CORE PROPERTIES			
Material	Polystyrene	Polystyrene	
Thickness	0.25 in	6.35 mm	
Compressive Strength	10,800 lbs/ft ²	527 kN/m ²	ASTM D-1621 (Mod.)
PRODUCT PROPERTIES			
Flow Capacity per unit width	9 gal/min/ft	112 L/min/m	ASTM D-4716
Roll length	50 ft	15.24 m	
Roll width	4 ft	1.22 m	
Roll weight	29 lbs	14 kg	

All information, drawings and specifications are based on the latest product information available at the time of printing. Constant improvement and engineering progress make it necessary that we reserve the right to make changes without notice. All physical properties are typical values. Standard variations in mechanical properties of 10% and in hydraulic properties of 20% are normal.



AMERICAN WICK DRAIN CORPORATION

1209 Airport Road • Monroe, NC • 28110, USA
800 242-WICK • 704 238-9200 • Fax 704 296-0690
www.americanwick.com • info@americanwick.com