




About Us **Products** **Engineering Info** **Contact Us** **Request Info**

Preformed Butyl Mastic Sealant

Preformed Butyl Mastic Sealants

	<p>NPC's Bidco C-56 Joint Sealant system is custom engineered to meet the most exacting standards of the precast concrete industry.</p>	<p>Technical Specifications</p>
---	---	---

C-56 remains flexible and forms a permanent bond to a wide variety of substrates including concrete, metals and plastics. Adhesion and cohesion at the time of installation are excellent, and actually improve after the joint has been formed and placed in service. This sealant is designed not to shrink, oxidize or harden and has excellent resistance to temperature extremes, acid and alkaline environments.

C-56 Butyl Joint Sealant is designed to fully comply with current ASTM Standards and specifications as required by Federal, State and Local agencies for use by the precast concrete industry and contractors.

Product Features:

- Available in strip or coil form
- Non-stick, non-tear plastic backing
- New, crush-proof packaging

Primary Applications:

- | | |
|---------------------------------|-----------------------------|
| Concrete Pipe | Box Culverts |
| Utility Vaults | Burial Vaults |
| Septic Tanks | Wet Wells |
| Sanitary & Storm Sewer Manholes | Concrete Wall Panel Systems |

Available Standard Sizes:

COILS				
Width & Length	Cross Section	Pieces Per Carton	Linear Feet Per Carton	Pallet Size # Cartons/ lbs.
.5" x 21.0'	oval	10	210	45 ctns. / 24 lbs.
.75" x 14.5'	.66 x .66	10	145	45 ctns. / 36 lbs.
1.0" x 14.5'	.88 x .88	8	116	45 ctns. / 50 lbs.
1.25" x 14.5'	.78 x 1.38	5	72.5	45 ctns. / 49 lbs.
1.5" x 10.0'	1 1/8 x 1.5	5	50	45 ctns. / 49 lbs.
2.0" x 10.0'	2.5 x 2 1/6	4	40	45 ctns. / 68 lbs.
FLATPACK STRIPS				

.75" x 30"	.478 x 1.0	50	125	36 ctns. / 35 lbs.
1.0" x 30"	.58 x 1.6	35	87	36 ctns. / 37 lbs.
1.25" x 42"	.5 x 2.5	28	98	36 ctns. / 71 lbs.
1.5" x 42"	.75 x 2.5	20	70	36 ctns. /75 lbs.
1.75" x 42"	.75 x 3.25	13	45	36 ctns. / 61 lbs.
2.0" x 42"	1.0 x 3.25	10	35	36 ctns. / 65 lbs.

*Custom sizes are available

NPC Bidco Butyl Wrap

To provide that extra measure of protection, NPC offers the Bidco Wrap. The wrap is applied externally to joints to stop infiltration in manholes, box culverts, septic tanks and other jointed precast structures. It is easy to apply and available in widths to fit most any application. It should be used in conjunction with an adhesive primer if wet conditions are present.

To meet the widest variety of applications, Bidco Wrap is available on a plastic or rubber backing with a durable, non-stick plastic release.

Bidco Wrap is available in 50' foot lengths in the following widths: 6", 8", 9", 10" and 12".

[Home](#) | [About NPC](#) | [Contact Us](#) | [Engineering Info](#)