



**Midwest
Construction
Products**

P.O. Box 727 277 N. Collier Blvd.
Marco Island, FL 34146

sediment fence
OK NASHTO 200 for 4' max

Phone: 239-642-0556 Fax: 239-642-6980
www.midwestconstruct.com

STYLE 1210 SILT FENCE (DATA SHEET)

THIS IS TO CERTIFY THAT STYLE (1210 SILT FENCE) AS MANUFACTURED AND SOLD BY WILLACOOCHEE INDUSTRIAL FABRICS, MEETS THE FOLLOWING MINIMUM SPECIFICATIONS.

TYPICAL MATERIAL	POLYPROPYLENE
COLOR	BLACK
CONSTRUCTION	12 EPI X 11 PPI
WEIGHT, OZ/ SY.	3.1
TENSILE STRENGTH, LBS.	124 WARP X 124 FILL
ELONGATION	15 %
MULLEN BURST	300 LB.
PUNCTURE	65 LB.
TRAPEZOIDAL TEAR	65 LB.
AOS	# 30 SIEVE
FLOW RATE	10 GAL/MIN SQ/FT
UV RESISTANCE	80 % AFTER 500 HOURS
STRENGTH RETENTION	

Larry Booth
Quality Control Manager



Sara Drake, CPESC
Outside Sales
816-805-9476 (CELL)

2440 West Pennway
P.O. Box 412676
Kansas City, MO 64141

816-471-2570 (OFFICE)
800-444-2570
816-421-1627 (FAX)

carter-waters.com
sdrake@carter-waters.com

Illinois Kentucky Tennessee Alabama Indiana Florida