



- PRETECH CORPORATION IS AN NPCA CERTIFIED PLANT
- ALL DIAMETERS ARE GASKET JOINT
- 15", 18", 24", 30", and 36" are Single Bevel Offset Joint

PRETECH CORP. REINFORCED CONCRETE PIPE MEETS OR EXCEEDS:

- ASTM C-76
- AASHTO M170

GASKET JOINT MEETS

- ASTM C443
- ASTM C361

FOR COMPLETE DESIGN AND PRODUCT DESIGN INFORMATION CONTACT PRETECH CORP.

PRETECH CORP. reserves the right to make changes to product design and/or dimensions without notice.

Please contact Pretech Corp. for confirmation or advice for your project design. Specialty pieces and designs are available, upon request.

'A' INSIDE DIAMETER	'B' LAY LENGTH	'C' WALL THICKNESS	'D' PIPE O.D.	'E' BELL O.D.	'F' JOINT DEPTH	AREA PER FT ²	WALL TYPE	CLASS	Wt/ft	PRODUCT WEIGHT
15" RCP	8'- 0"	2.25"	19.5"	24"	3.625"	1.2 ft ²	B	IV & V	136 lbs	1,125 lbs
18" RCP	8'- 0"	2.5"	23"	27.875"	3.625"	1.8 ft ²	B	III to V	183 lbs	1,520 lbs
24" RCP	8'- 0"	3"	30"	35.5625"	3.875"	3.1 ft ²	B	III to V	289 lbs	2,410 lbs
30" RCP	8'- 0"	3.5"	37"	42.625"	4"	4.9 ft ²	B	III to V	410 lbs	3,420 lbs
36" RCP	8'- 0"	4"	44"	50.375"	4.125"	7.1 ft ²	B	III to V	568 lbs	4,740 lbs

PIPE IS FURNISHED WITHOUT LIFT HOLES. LIFT HOLES CAN BE FURNISHED, UPON REQUEST.