



Submittal Specification

The joints and/or joint surfaces of the structures shall be sealed with a butyl-rubber-based preformed flexible sealant conforming to ASTM C-990, paragraph 6.2. The material shall be PRO-STIK or EZ-STIK as supplied by PRESS-SEAL CORPORATION, Fort Wayne, Indiana, or approved equal. The butyl material shall consist of 50% (min.) butyl rubber and shall contain 2% or less volatile matter.

For preformed joint sealants, the sealant shall be sized such that the joint is filled to 50% (min.) of its annular volume when fully assembled, and the sealant shall have the ends kneaded together at the overlap. Primer and/or adhesive as recommended by the sealant supplier shall be employed for adverse, critical, or other applications.

Testing of joints and compliance with construction requirements shall be conducted in strict conformance with the requirements of the sealant supplier.

PRO-STIK AVAILABLE SIZES

1/2"
.45 x .45
11 x 11 mm

1/2" x 3/4"
.50 x .75
13 x 19 mm

3/4"
.60 x .80
15 x 20 mm

1"
.75 x 1.05
19 x 27 mm

1 1/4"
.88 x 1.40
22 x 36 mm

Dimensions		Round Equivalent	Roll Length		Rolls per Carton	Cartons per Pallet	Part No.
INCH	mm		FEET	Meter			
.45 X .45	11 x 11 mm	1/2"	21.75 ft	6.95 m	12	24	279.1
.45 X .45	11 x 11 mm	1/2"	26.4 ft	8.44 m	12	24	279.1A
.50 X .75	13 x 19 mm	1/2" X 3/4"	21.75 ft	6.95 m	8	40	288.33
.60 X .80	15 x 20 mm	3/4"	14.5 ft	4.64 m	8	40	279.2B
.75 X 1.05	19 x 27 mm	1"	14.5 ft	4.64 m	6	40	279.3
.88 X 1.40	22 x 36 mm	1-1/4"	14.5 ft	4.64 m	4	40	279.4C

All pallets are shrink-wrapped for outside storage.
Quantity discounts available - contact our Customer Service Department.

Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2012.