

Splice Closure Fiber (SCF), preloaded with splice trays

72 single-fiber splice capacity, 6-in diameter, 22-in dome length

CORNING

Corning Splice Closure (SCF) with Mechanical End Cap is designed for splicing fibers in aerial, duct and buried applications. These sealed canister closures are available in configurations that can accommodate from 72 to 576 single fiber splices, or from a 288- to 1296-fiber capacity if splicing ribbons.

Features and Benefits

Modular fiber management system
Increased splicing capability in the field

Aerial, wall, pole, direct-buried
Suitable for all applications

Ribbon reel-end to reel-end splicing
No additional splice trays required (ORS)

Split end caps
Easy installation of uncut cables



Specifications

General Specifications	
Application	Customer premises environments, Carrier Networks, CATV environments
Mounting Type	Pole-mount, Wall-Mountable
Product Type	FOH Closures

Design - Hardware	
Fiber Management Configuration	Full slack storage basket - tray stacker
Ground Feed Through Cable Entries	1
Number of Feeder Ports	2 2 / 6 ports: 2 feeder ports and 4 drop ports
Number of Ports	6
SCF Type	6-inch canister, 22 in LID
Splicing Capacity	72
Splice Tray Stacker Configuration	0.2-in tray height (single fiber)

Mechanical Characteristics	
Dimensions: Diameter and Length	16.8 cm x 56 cm 6.6 in x 22 in
Outside Diameter with Clamp	7.8 in (20 cm)

Splice Closure Fiber (SCF), preloaded with splice trays

72 single-fiber splice capacity, 6-in diameter, 22-in dome length



Ordering Information

Part Number	SCF-6C22-01-72
Product Description	Splice Closure Fiber (SCF), preloaded with splice trays, 72 single-fiber splice capacity, 6-in diameter, 22-in dome length
EAN Code	4056418189970

Shipping Information

Units per Delivery	1/1
--------------------	-----

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.