

# Closet Connector Housing (CCH) One rack unit, holds two CCH connector panels

CORNING

## Part Number: CCH-01U

Closet connector housings (CCHs) provide interconnect or cross-connect capabilities between outside plant, riser or distribution cables and opto-electronics. Like other LANscape solutions hardware, the housings accept CCH connector panels. In addition, the housings accept CCH cassettes and CCH modules.

From fiber and cable routing and strain relief, to port labeling and termination, these housings reduce the risk of error that can disrupt networks. The units are designed for rack mounting in 19-in (48 cm) racks or optional 23-in (58 cm) equipment racks (1.75-in EIA hole spacing). They are available in rack space options of 1U (two panels, cassettes or modules), 2U (four panels, cassettes or modules), 3U (six panels, cassettes or modules) and 4U (12 panels, cassettes or modules). The 1U, 2U and 3U options feature a slide-out tray and see-through, removable top covers. The CCH-04U features a clear door, removable front and rear enclosures and a platinum-colored interior for maximum visibility and access.

Every CCH housing is shipped complete with strain relief brackets, routing clips and guides, and mounting brackets for proper installation. Documentation labels are provided and components can be added as needed to construct a fiber distribution frame for any application. All housings include a removable tinted polycarbonate front door.



Closet Connector Housing (CCH), one rack unit, holds two CCH connector panels

## Features and Benefits

### **Durable, polycarbonate-tinted front door for viewing jumpers**

Ideal for pigtail splicing

### **Removable, translucent top covers (1U, 2U, 3U), removable rear cover (4U)**

Visibility and ease of access for installation, testing, and troubleshooting

### **Internal and external strain-relief options**

Flexibility for installation and moves, adds, and changes (MACs)

### **Accepts panels, modules, and cassettes**

Variety of field-termination options

### **Adaptable to use as a modular splice housing**

Splices are stored and protected in same footprint

# Closet Connector Housing (CCH) One rack unit, holds two CCH connector panels



## Specifications

Design	
Fiber Count	48
Housing Material	Powder-coated metal and polycarbonate tray
Cable entry type	External and Internal strain-relief bracket
Pigtail Length	2.25 m (7.38 ft)
Housing Type	CCH
Locking Availability	Front or rear
Panel or Module Type	CCH
Splice Tray Options	CCH Splice Cassette (CCH-CS)
Number of Ports	24

General Specifications	
Product Type	Fiber Optic Hardware
Environment	Indoor
Access Type	Front and rear access slidable
Lockable	Yes
Mounting Type	Rack 19-in, Rack 23-in, Cabinet-mount
Application	Carrier Networks, Data Center, Enterprise Networks

Shipping Dimensions	
Height	54.61 cm
Width	57.15 cm
Depth	19.05 cm

Environmental Conditions	
Temperature Range, Operation	-40 °C to 70 °C (-40 F to 158 F )

# Closet Connector Housing (CCH) One rack unit, holds two CCH connector panels

CORNING

## Ordering Information

Product Number	CCH-01U
EAN Code	4056418169491
Weight	3.9 kg
Shipping Weight	4.5 kg
Units per Delivery	1/1

## Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	Meets ANSI/TIA/EIA-568A and 606, Tested in accordance with Telecordia GR-63-CORE, UL1863 - Communication Circuit Accessories
UL-Listed	United States and Canadian safety standards



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2022 Corning Optical Communications. All rights reserved.