

# Integrated Single-Panel Housing

12 F, bottom-mounted OptiTip® adapter, front-mounted ST® compatible adapters, Single-mode (OS2)

CORNING

Many of our fiber optic hardware products are highly configurable. If you don't see what you are looking for here, please review the ordering matrix contained in the family spec sheet found on the right, or contact Customer Care at 1-800-743-2675.

Corning Integrated single-panel housing utilizes the OptiTip® adapter with the small-profile single-panel housing for quick and easy deployment eliminating the need for field-terminated and strain-relieved fiber optic cables. The housing is ideal for star, ring, point-to-point, or zone architectures. Factory-terminated panels provide industry-leading quality and reliability while eliminating the time required for field-termination methods and the need for specialized field-termination tools, training, and specially prepared locations. The compact unit is ideal for use inside NEMA- and IP rated enclosures and other environments where space is a premium.



## Features and Benefits

### Factory terminated

Eliminates need for field termination, improving reliability and speed of deployment; faster, easier installation and moves, adds and changes

### Configurable in 12 and 24 fibers, single-mode and multimode, supporting SC, LC and ST® compatible connectors

Network flexibility

## Specifications

General Specifications	
Application	Enterprise Networks
Mounting Type	Wall-Mountable
Product Type	AnyLAN Housings and Modules
Fiber Category	Single-mode (OS2)

Design - Hardware	
OptiTip® Adapter Placement	Bottom-mounted
Connector Polish	UPC
Connector Type	ST® Compatible
Fiber Count	12

CORNING

# Integrated Single-Panel Housing

12 F, bottom-mounted OptiTip® adapter, front-mounted ST® compatible adapters, Single-mode (OS2)



## Mechanical Characteristics

Dimensions (HxWxD)	16.5 cm x 15.2 cm x 3.8 cm (6.5 in x 6 in x 1.5 in)
--------------------	---

## Design Adapter

Adapter Style	Standard
Adapter Type	ST® Compatible

## Ordering Information

Part Number	SPH-12OTR-126TH
Product Description	Integrated Single-Panel Housing, 12 F, bottom-mounted OptiTip® adapter, front-mounted ST® compatible adapters, Single-mode (OS2)
EAN Code	4056418178479

## Shipping Information

Shipping Weight	0.7 kg (1.5 lb)
Units per Delivery	1/1
Package Contents	Housing; installation guide; label, unit ID; 2 mounting brackets; 2 screws, 10-32 x .25; 2 screws, 8-18 x .625; 4 screws, 6-32 x .25 and 4 screws, 6-32 x .312



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.