

# PUSH-LOCK

www.duraline.com



Customer Service  
800-847-7661



## FEATURES:

- Simple, one person 'push-on' assembly lowers installation costs
- Self-locking ring design assembles in seconds; is re-enterable
- High strength molded plastic body ideal for buried duct applications
- Pre-lubricated O-ring is water and air tight suitable for both cable pulling & jetting applications

Installation is fast and easy; no heat or tools are needed. Simply push the duct ends into the coupler for a locked and air-sealed assembly. The compact profile of the PUSH-LOCK is well suited for use in pull boxes, vaults, or other limited-access areas such as narrow trenches. The non-metallic construction provides excellent corrosion resistance in buried or encased applications and also has desirable dielectric properties. The PUSH-LOCK is non-transparent and contains UV inhibitors, but is not recommend for aerial applications.

Part Number	Size	Nominal OD	Duct OD Working Range	Color	Length	Tensile Pullout (lbs) MIN-MAX	Max Pressure (PSI)	Carton Quantity	Weight per Carton (lbs)
20001844	1"	1.315"	1.305-1.325"	Orange	3.5"	600-800	250	50	11
20001845	1 1/4"	1.660"	1.650-1.670"	Orange	5"	700-900	250	50	22.5
20001846	1 1/2"	1.900"	1.890-1.910"	Orange	5.5"	800-1000	250	25	15
20001847	2"	2.375"	2.365-2.385"	Orange	7.5"	2000-2400	250	25	35



Part Number	Size	Nominal OD	Duct OD Working Range	Color	Length	Tensile Pullout (lbs) MIN-MAX	Max Pressure (PSI)	Carton Quantity	Weight per Carton (lbs)
1-909075	1/2"			Off White					
20001491	3/4"	3/4"		Off White			230	144	4.4