



# Ground Rod Clamp, Rod to Conductor, Bronze



- For use with copper-bonded ground rods
- Parts that are UL Listed are suitable for direct burial in earth or concrete



Material: Silicon Bronze

| Part Number             | Ground Rod Diameter, Nominal | Ground Rod Diameter, Actual $\varnothing$ | Conductor Size   | Wrench Size | Certifications |
|-------------------------|------------------------------|---|--|-------------|----------------|
| Torque: 150 – 300 in lb |                              |   |  |             |                |
| CP38                    | 3/8"                         | 0.38"                                     | #10 Solid - #2 Stranded,<br>6 mm <sup>2</sup> Solid - 25 mm <sup>2</sup> Stranded  | 3/8"        | cULus          |
| CP58                    | 1/2" – 5/8"                  | 0.50" – 0.56"                             | #10 Solid - #2 Stranded,<br>6 mm <sup>2</sup> Solid - 25 mm <sup>2</sup> Stranded  | 1/2"        | CSA, cULus     |
| CP34                    | 1/2" – 3/4"                  | 0.50" – 0.68"                             | #10 Solid - 1/0 Stranded,<br>6 mm <sup>2</sup> Solid - 50 mm <sup>2</sup> Stranded | 1/2"        | CSA, cULus     |
| Torque: 150 – 450 in lb |                              |   |  |             |                |
| HDC12                   | 1/2"                         | 0.50"                                     | #10 Solid - #2 Stranded,<br>6 mm <sup>2</sup> Solid - 25 mm <sup>2</sup> Stranded  | 1/2"        | CSA, cULus     |
| HDC58R                  | 5/8"                         | 0.56"                                     | #8 Solid - 1/0 Stranded,<br>10 mm <sup>2</sup> Solid - 50 mm <sup>2</sup> Strand   | 1/2"        | CSA, cULus     |
| HDC58                   | 5/8"                         | 0.56"                                     | #8 Solid - 1/0 Stranded,<br>10 mm <sup>2</sup> Solid - 50 mm <sup>2</sup> Stranded | 9/16"       | CSA, cULus     |
| HDC34                   | 3/4"                         | 0.68"                                     | #8 Solid - 1/0 Stranded,<br>10 mm <sup>2</sup> Solid - 50 mm <sup>2</sup> Strand   | 9/16"       | CSA, cULus     |
| HDC34SP                 | 3/4"                         | 0.68"                                     | #8 Solid - 3/0 Stranded,<br>10 mm <sup>2</sup> Solid - 70 mm <sup>2</sup> Stranded | 9/16"       | CSA            |
| HDC1                    | 1"                           | 1.00"                                     | #8 Solid - 4/0 Stranded,<br>10 mm <sup>2</sup> Solid - 95 mm <sup>2</sup> Strand   | 9/16"       | cULus          |

CSA, CSA-US and C-CSA-US are registered trademarks of Canadian Standards Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 nVent. All rights reserved.

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.