




Liquidtight Flexible Nonmetallic Conduit

TYPE - NM



Contact your local Sales Representative
[Click Here for Printable Version](#)

				Coil	Footage	Reel		List Price
Trade Size	Type	Inside Bend Radius	Wt. (Lbs.)/100 Ft.	Length	Part #	Length	Part#	Price Per 100 FT
3/8"	NM -10	2.0"	10	100	81001	1000	81004	\$143.00
1/2"	NM -11	3.25"	11	100	81011	1000	81014	\$146.00
3/4"	NM -12	4.25"	15	100	81022	500	81024	\$197.00
1"	NM -13	6.5"	25	100	81032	400	81034	\$311.00
1-1/4"	NM -14	8.0"	34	100	81042			\$435.00
1-1/2"	NM -15	9.0"	42	50	81052			\$563.00
2"	NM -16	11.0"	60	50	81062			\$781.00



NM Type B

See [Chart for Dimensions and Tolerances](#).

*Also available on reels. Please consult factory

TYPE - NM

A general purpose nonmetallic liquidtight conduit offers excellent protection to wiring from abrasion, sunlight, mild acids, alkaline and oils. Often used for air conditioning hook-ups and other outdoor applications.

CONSTRUCTION:

NM is a helically wound integral Type B construction. It contains a spiral of rigid PVC reinforcement imbedded within the PVC wall.


APPLICATION:

Type NM is intended for installation in accordance with Article 356 of the NEC® (ANSI/NFPA-70) for Flexible Liquidtight Nonmetallic Conduit (LFNC-B or FNMC-B).

- For containment of 600 volt and lower potential circuits.
- Listed and Marked for Outdoor Use.

- Listed and Marked for Direct Burial and in Poured Concrete
 - Installations in hazardous (classified) locations:
Class I Div. 2 Article 501
Class II Div. 1 & 2 Article 502
Class III Div. 1 & 2 Article 503
 - Electric Signs and Outdoor Lighting over 1000 volts. Article 600.32(A)
 - Wiring methods for pools and spas. Article 680.
- Conforms to the requirements of section 14.5.5 of the Electrical Standard for Industrial Machinery NFPA-79.

 Listed File # E 79308
Conforms to Underwriters Laboratories Standard ANSI/UL 1660 type B

 Certified File #LL 230485
Conforms to CSA 22.2 No. 227.2 type B

Fittings:

Suitable for use with nonmetallic fittings marked for FNMC-B or LFNC-B for Liquidtight Flexible Nonmetallic Conduit type B or with standard metal liquidtight fittings. See NMLT Connectors for further information.

Tests Include:

[WEEE and RoHS Compliant](#)

STANDARD COLORS:

Machine Tool Gray and Black. [Other colors available upon request](#)

WORKING TEMPERATURES:

-20°C to 80°C Dry / 60°C Wet / 70°C Oil
For higher temperature version, see type NMHT

Flexibility: [See the Flexibility Comparison Guide](#)

Plastic Used: PVC [See the Chemical Resistance Guide](#)

High Mech. Strength	Listed For Direct Burial	Halogen Free	Low Fire Hazard	Accepts Standard Liquidtight Fittings	Self Extinguish	EMI/RFI Shielding	Oil Resistance	Acid Resistance
X	X				X		X	X