



ITW Strapbinder stainless steel banding is available in Type 201, 304, or 316 stainless steel. Strapbinder band, ideal for large diameter hose assemblies and sign securement, is made with a full round edge for safer handling.

Type 201 Stainless Steel

Type 201 stainless steel has excellent mechanical properties and strength. Due to its high work hardening rate, it possesses uniform elongation for improved stretchability for severe forming applications such as strapping bands and preformed hose clamps.

Type 304 Stainless Steel

Type 304 stainless steel is an 18% chromium and 8% nickel alloyed stainless steel. Used most often in outdoor industrial applications, it offers good corrosion resistance and is weldable.

Type 316 Stainless Steel

Type 316 stainless steel provides superior corrosion resistance, making it ideal for use near salt water and petrochemical facilities.



Catalog No.	Width		Type	Thickness		Weight		Qty/Coil		
	inch	mm		inch	mm	lbs	kg	ft	M	
100 ft. Self Dispensing Coils										
ST202	1/4	6.3	201	.020	.51	1.7	0.9	100	30	
ST203	3/8	9.5	201	.025	.63	3.2	1.6	100	30	
ST204	1/2	12.7	201	.030	.76	5.1	2.4	100	30	
ST205	5/8	15.8	201	.030	.76	6.4	3.0	100	30	
ST206	3/4	19.0	201	.030	.76	7.7	3.6	100	30	
ST404	1/2	12.7	316	.030	.76	5.1	2.4	100	30	
ST405	5/8	15.8	316	.030	.76	6.4	3.0	100	30	
ST406	3/4	19.0	316	.030	.76	7.7	3.6	100	30	



Catalog No.	Width		Tote Color	Thickness		Weight		Qty/Coil		
	inch	mm		inch	mm	lbs	kg	ft	M	
100 ft. Plastic Totes (Type 201 Stainless Steel)										
ST204B	1/2	12.7	Blue	.030	.76	5.1	2.4	100	30	
ST205G	5/8	15.8	Green	.030	.76	6.4	3.0	100	30	
ST206R	3/4	19.0	Red	.030	.76	7.7	3.6	100	30	



200 ft. Economy Coils for Light Duty Applications										
ST128/904	1/2	12.7	304	.015	.38	5.5	2.5	200	61	
ST183/914	1/2	12.7	304	.020	.51	7.0	3.2	200	61	
ST184	1/2	12.7	304	.025	.63	6.4	3.0	200	61	
ST129/905	5/8	15.8	304	.020	.51	8.5	3.6	200	61	
ST163/916	3/4	19.0	304	.020	.51	11.2	5.1	200	61	
ST165	3/4	19.0	304	.025	.63	12.7	5.8	200	61	



Bigbinder Band										
ST430	3/4	19.0	201	.044	1.12	11.6	5.4	100	30	
ST431	1	25.4	201	.044	1.12	13.7	6.4	100	30	
ST432	1-1/4	31.8	201	.044	1.12	17.2	8.0	100	30	



Mill Wound Coils										
BLCPX04155	1/2	12.7	Oscillate	.015	.38	100	45.4	3,920	1195	
305SSR900	1/2	12.7	Ribbon	.020	.51	30	13.6	900	274	
305SSV3000	1/2	12.7	Oscillate	.020	.51	100	45.4	3,000	914	
BLCPX05202	5/8	15.8	Oscillate	.020	.51	100	45.4	2,300	701	
311SSR900	3/4	19.0	Ribbon	.020	.51	42	19.1	900	274	
311SSV2000	3/4	19.0	Oscillate	.020	.51	100	45.4	2,000	610	