

USE-2

XLP Insulation Underground Service Cable



Type RHH-90°C (Dry)

Type RHW-2-90°C
(Wet or Dry)

600 volts

Sequential
foot markings 

Rated for CT use (1/0
and larger)

Sunlight resistant
in black



MADE IN THE USA

©2012, Cerro Wire LLC
All Rights Reserved

APPLICATIONS

For use in conduit or suitable for use as underground service entrance cable for direct burial per NEC®. Good choice for industrial applications where better insulation toughness and resistance to moisture and heat are desired. For use as RHH or RHW-2 in wet or dry locations at temperatures up to 90°C. Sunlight-resistant (black only). For CT use on 1/0 and larger. Gas and Oil Resistant II.

CONDUCTORS

Stranded conductors: Uncoated, soft copper per ASTM-B3 and ASTM-B8.

INSULATION

XLP (cross-linked polyethylene). Printed with True Sequential Footage.

INDUSTRY STANDARDS*

UL 44 (RHH or RHW-2), File No. E125474

UL 854 (USE-2), File No. E11098

ASTM-B3

ASTM-B8

Federal Specification A-A-59544

NFPA70: National Electrical Code®

NEMA WC70/ICEA S-95-658

RoHS Compliant

SURFACE PRINT

**Sample (14-10 AWG): CERROWIRE-U 12 AWG (3,31mm²) (UL) USE-2 OR RHH OR RHW-2 GRII SR 600V XL

**Sample (8-1 AWG): CERROWIRE-U 2 AWG (33,6mm²) (UL) USE-2 OR RHH OR RHW-2 GRII SR 600V XL

**Sample (1/0-750 MCM): CERROWIRE-U 400 MCM (203 mm²) (UL) USE-2 OR RHH OR RHW-2 GRII FOR CT USE SR 600V XL

**For black. "SR" is omitted for colors other than black.



*It is the sole responsibility of the end user to determine suitability of this product for its intended end use and application.

cerrowire

Electrical Distribution Division: 800.523.3869 | FAX 877.877.9563
Consumer Markets Division: 866.572.3776 | FAX 812.793.2626
www.cerrowire.com

A Marmon Group/
Berkshire Hathaway Company

USE-2

XLP Insulation

Underground Service Cable

Product Code Number	Conductors		Insulation Thickness Mils.	Approx. O.D. Inches	Allowable Ampacities*			Approx. Net Wt. Lbs./M Ft.
	AWG Size	No. of Strands			60°C **	75°C ***	90°C ****	
NEW 1201-24xx	14	7	45	0.160	15	15	15	21
NEW 1201-26xx	12	7	45	0.180	20	20	20	29
NEW 1201-28xx	10	7	45	0.200	30	30	30	42
1201-40xx	8	7	60	0.280	40	50	55	65
1201-42xx	6	7	60	0.320	55	65	75	102
1201-44xx	4	7	60	0.370	70	85	95	154
1201-45xx	3	7	60	0.400	85	100	115	192
1201-46xx	2	7	60	0.430	95	115	130	236
1201-47xx	1	19	80	0.500	110	130	145	307
1201-5001	1/0	19	80	0.540	125	150	170	379
1201-5201	2/0	19	80	0.590	145	175	195	466
1201-5401	3/0	19	80	0.640	165	200	225	580
1201-5601	4/0	19	80	0.700	195	230	260	719
1201-6001	250	37	95	0.780	215	255	290	861
1201-6401	300	37	95	0.840	240	285	320	1,015
1201-6801	350	37	95	0.880	260	310	350	1,183
1201-7201	400	37	95	0.920	280	335	380	1,335
1201-8001	500	37	95	1.010	320	380	430	1,658
NEW 1201-8401	600	61	110	1.100	355	420	475	2,000

xx Color add code is as follows: Black - 01, White - 02, Red - 03, Blue - 04, Green - 05, Orange - 06, Yellow - 07, Brown - 08, Gray - 10, 1/0 & larger - Black only.

* Per Table 310.15 (B) (16) NEC®

** For termination to equipment for circuits rated 100 amperes or less or marked for size 14 through 1 AWG conductors.

*** For termination to equipment for circuits rated over 100 amperes or marked for conductors larger than 1 AWG.

**** RHH in dry locations. RHW-2 and USE-2 in wet or dry locations.

USE-2

XLP Insulation

Underground Service Cable

Package Code	J	K	L	R	M	P
AWG Size	500' Reel	1,000' Reel	1,500' Reel	2,000' Reel	2,500' Reel	5,000' Reel
14	X				X	
12	X				X	
10	X				X	
8		X				X
6		X				X
4		X				X
3		X				X
2		X				X
1		X				X
1/0		X				X
2/0		X				X
3/0		X				X
4/0		X				X
250 MCM		X			X	
350 MCM		X			X	
400 MCM		X		X		
500 MCM		X			X	
600 MCM		X		X		