

# Rigid Non Metallic Schedule 40 Electrical Conduit

## Schedule 40 Electrical Conduit

Heritage Plastics created the long bell for ease and efficiency. In compliance with the industry standards, Heritage Plastics PVC Electrical Conduit is manufactured from PVC compounds complying with the UL651 standards. Our PVC Electrical Conduits are subject to in-process quality control to assure compliance with appropriate manufacturing and performance standards.

- UL 651
- NEMA TC-2
- Sunlight resistant per UL 651
- Listed for 90° C conductors or cable
- Rigid nonmetallic raceway for wires and cables in accordance with the NEC



10' Part No.	20' Part No.	Trade Size	Average O.D. (in)	Minimum Average I.D. (in)	Minimum Wall (in)	Weight Per Foot (lbs)	10 Ft Crate Quantity (ft)
8102	8502	½	0.840	0.578	0.109	0.165	6000
8103	8503	¾	1.050	0.780	0.113	0.220	4400
8104	8504	1	1.315	1.004	0.133	0.326	3600
8105	8505	1 ¼	1.660	1.335	0.140	0.441	3300
8106	8506	1 ½	1.900	1.564	0.145	0.528	2250
8108	8508	2	2.375	2.021	0.154	0.730	1400
8110	8510	2 ½	2.875	2.414	0.203	1.158	930
8112	8512	3	3.500	3.008	0.216	1.609	880
8114	8514	3 ½	4.000	3.486	0.226	1.935	630
8116	8516	4	4.500	3.961	0.237	2.292	570
8120	8520	5	5.563	4.975	0.258	3.105	380
8124	8524	6	6.625	5.986	0.280	4.030	260
880747	924297	8*	8.625	7.853	0.322	6.065	140

Meets or exceeds the requirements of **NEMA TC 2** and **UL 651** for Schedule 40 Conduit.

\* UL 651 does not include 8"

