



HOMAC

Flood-Seal Multi-Port Connectors T&B Catalog Number:

UPC Number: Status: Description: RAB 1/0-21 78378674489 Active

Aluminum Flood-Seal Multi-Port Connectors - RAB 1/0 Series, length 2-39/64 inch, outlets 3, 2 on one side, 1 on the other.

Features

	Flood-Seal Insulating Rockets- serve as waterproof spare outlet caps until used. Rockets are also re- sealable.
	6061-T6 Aluminum Connector Construction pro- vides high strength and high conductivity.
	All Connectors are 100% Hi-Pot tested at 4000V for
	60 seconds. Ensures that connectors are 100% wa-
	tertight and molded correctly.
	RAB 1/0 Series Offers Compact Design which is
	great for streetlight applications.
General	
Style	Lighting Mechanical Connectors
Material	Aluminum
Conductor Range	14-1/0
Outlets	3
Dimension Information	
Length (inches)	2 39/64
Notes	
	For oxide-inhibitor option, add "-C" suffix to the cat- alog number.
	For EZ Torque (shear-head screws) supplied in all outlets, add "-TS" suffix to the catalog number.
Certifications	
Standards Compliant	RUS Accepted.
RUS	Y

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com