

## Grounding

### Ground Rod Clamps

**CIGRC58**



Cat. No.	Water Pipe Size	Dimensions (in.)		Galv. Steel (in.)	Copper Clad (in.)
		Min.	Max.		
<b>Ground Rod Clamps (Bronze body / brass screws)</b>					
<b>CIGRC58</b>	N/A	10 sol.	2 str.	5/8	5/8
<b>CIGRC34</b>		8 sol.	1/0 str.	3/4	3/4

For connecting grounding conductor to either galvanized steel rod or copper clad rod  
CSA certified for wet locations and for direct burial

**JAB12**



Cat. No.	Dimensions (in.)		Dimensions (in.)				Thread Size UNC-2A
	in.	mm	Min.	Max.	Min. (mm <sup>2</sup> )	Max. (mm <sup>2</sup> )	
<b>Ground Rod Clamps</b>							
<b>Socket Type</b>							
<b>JAB12</b>	1/2	12.7	10 sol.	2 str.	5.2	33.6	7/16-14
<b>JAB34C</b>	3/4+5/8	15.8	8 sol.	3/0 str.	8.3	95.0	7/16-14
<b>JAB1</b>	1	25.0	8 sol.	4/0 str.	8.3	107.1	7/16-14
<b>Hex Head Bolt</b>							
<b>JAB12H</b>	1/2	12.7	10 sol.	2 str.	5.2	33.6	7/16-14
<b>JAB58H</b>	5/8	15.8	8 sol.	1/0 str.	8.3	53.4	7/16-14
<b>JAB34H</b>	3/4	19.0	8 sol.	1/0 str.	8.3	53.4	7/16-14
<b>JAB1H</b>	1	25.0	8 sol.	4/0 str.	8.3	107.1	7/16-14

Cast of high strength corrosion-resistant copper alloy. Both hex head and socket set screw available. Long bearing surface of clamp on ground wire secures ground connection UL listed for direct burial.

**G3**



Cat. No.	Dimensions (in.)		Dimensions (in.)				Thread Size UNC-2A
	in.	mm	Min.	Max.	Min. (mm <sup>2</sup> )	Max. (mm <sup>2</sup> )	
<b>Type G - Budget Line Ground Rod Clamps</b>							
<b>G3*</b>	3/8	9.5	10 sol.	4 str.	5.2	21.1	5/16-18
<b>G4</b>	1/2	12.7	10 sol.	2 str.	5.2	33.6	3/8-16
<b>G5</b>	5/8	15.8	10 sol.	2 str.	5.2	33.6	3/8-16
<b>G6</b>	3/4	19.0	10 sol.	2 str.	5.2	33.6	3/8-16

A dependable ground connection offered at a substantial saving. Cast of high strength corrosion-resistant copper alloy. Hex head bolts. Simplified compact design will make a lasting trouble free connection UL listed for direct burial. \* Not CSA certified