

# POWER POST™, TELES PAR® & ANGLE IRON TYPE III BARRICADES

## Five Options Available

- Power Post™ uprights with Telespar® feet
- Power Post™ uprights with Angle Iron feet
- Telespar® uprights with Telespar® feet
- Telespar® uprights with Angle Iron feet
- Angle Iron uprights with Angle Iron feet

## Power Post™ Type III Barricade

- Plastic posts save you time and money!  
easier to handle; set up and break down goes faster
- Lightweight but strong plastic square tube  
67% lighter than steel square tube posts
- Impact resistant
- No rust or corrosion
- Uprights have holes for attaching boards and lights

### Telespar® Feet

- Feet are 14 gauge, galvanized, hot rolled high carbon steel

### Angle Iron Feet

- Feet are 10 gauge steel, mill finish

Plastic boards available in 4', 6', 8', 10', and 12' lengths  
- retroreflective sheeting on one or both sides

Quick removal of uprights from feet  
- allows for short term or permanent placement

Easy to assemble and replace parts if necessary

Accepts two flashing lights

Dimensions: Power Post™ Upright - 1.75" x 1.75" x 63" - 3 lbs.  
Telespar® Foot - 1.75" x 1.75" x 60", Riser - 6"H - 10 lbs.  
Angle Iron Foot - 1.5" x 1.5" x 60", Riser - 6"H - 7 lbs.

NCHRP-350/MASH Accepted, Meets MUTCD Standards



Power Post™  
plastic square tube post

## OPTION #1



## OPTION #2



# TELESPAR® & ANGLE IRON TYPE III BARRICADES

## Telespar®

- Square shape provides superior wind load capabilities and inhibits warping
- Uprights and feet are 14 gauge, galvanized, hot rolled high carbon steel
- Prepunched universal mounting holes - 7/16" dia.

## Angle Iron

- Uprights are 10 gauge, galvanized steel
- Holes for boards 11/32" dia. and holes for lights 9/16" dia.
- Feet are 10 gauge steel, mill finish

Plastic boards available in 4', 6', 8', 10', and 12' lengths  
- retroreflective sheeting on one or both sides

Quick removal of uprights from feet  
- allows for short term or permanent placement

Easy to assemble and replace parts if necessary

Accepts two flashing lights

Dimensions: Telespar® Upright - 1.75" x 1.75" x 63"  
Telespar® Foot - 1.75" x 1.75" x 60", Riser - 6"H  
Angle Iron Upright - 1.5" x 1.5" x 63"  
Angle Iron Foot - 1.5" x 1.5" x 60", Riser - 6"H

NCHRP-350 Accepted, Meets MUTCD Standards

## OPTION #3



## OPTION #4

Holes for mounting flashing lights



## OPTION #5



Type III Barricades are sold in kits with three boards with your choice of sheeting. Sheeting can be on one side of the boards or both. All hardware needed for assembly is included in the kit.