



### FEATURES:

- One person installation
- Re-enterable, no special tools required
- Air and water tight
- No I.D. reduction
- Excellent pull out strength on HDPE, PVC, FRP and steel
- No-Stop version available for confined areas or repairs (\*NS)
- ETL Listed
- Listed to CSA STD C22.2 18.3-04
- Listed to UL STD 514B

Plastic coupler designed for coupling HDPE & PVC conduit. Can also be used to couple dissimilar conduits such as HDPE to PVC, threaded or non-threaded metal conduit, or fiberglass (FRP) conduit. The coupler features stainless steel band clamps (hand tightened using a 5/16" nut driver) and locking ring. A pre-lubricated O-ring forms an air-tight seal to withstand 125 psi. Also, a specialized coupler for use by electrical installers requiring ETL/UL listing. **NOTE:** Certain sizes ETL-Listed for use with HDPE and PVC for underground and concrete encased applications only! Not for use with PVC in above-ground applications. Not premise (indoor) rated.

PART #	SHUR-LOCK II COUPLER		NOMINAL PULL-OUT STRENGTH	PACKAGING	SHIP WEIGHT (lbs)
20000118	1.00" Shur-Lock II Coupler SDR 1.315" ± 0.020"	ETL	600 lbs	10/CTN	5
20000119	1.00" Shur-Lock II Coupler HYB 1.350" ± 0.020"		600 lbs	10/CTN	5
20000120	1.25" Shur-Lock II Coupler SDR 1.660" ± 0.020"	ETL	700 lbs	10/CTN	6
20000121	1.25" Shur-Lock II Coupler HYB 1.590" ± 0.020"		700 lbs	10/CTN	6
20000177	1.25" Shur-Lock II Coupler 1.534" ± 0.020"		700 lbs	10/CTN	5
20000122	1.50" Shur-Lock II Coupler SDR 1.900" ± 0.020"	ETL	800 lbs	10/CTN	6
20000123	2.00" Shur-Lock II Coupler SDR 2.375" ± 0.020"	ETL	800 lbs	10/CTN	7
20000264	2.00" Shur-Lock II Coupler-Extended SDR 2.375" ± 0.020" (8.25" long vs 5.75" standard)		800 lbs	10/CTN	8
20000172	2.50" Shur-Lock II Coupler SDR 2.875" ± 0.020"	ETL	1,000 lbs	6/CTN	8
20000173	3.00" Shur-Lock II Coupler SDR 3.500" ± 0.020"	ETL	1,000 lbs	6/CTN	11
20000245	4.00" Shur-Lock II Coupler SDR 4.500" ± 0.020"	ETL	1,000 lbs	4/CTN	15
1-407004	4.00" Shur-Lock II Coupler SIDR 13.5 4.657" + 0.020"		1,000 lbs	4/CTN	15
20000254	5.00" Shur-Lock II Coupler SDR 5.563" ± 0.020"	ETL	1,000 lbs	2/CTN	18
20000256	6.00" Shur-Lock II Coupler SDR 6.625" ± 0.020"	ETL	1,000 lbs	2/CTN	20












ETL Please specify if ETL listing is required.



Specialized couplers for coupling dissimilar-sized ducts within the ranges specified.

PART #	SHUR-LOCK II COUPLER TRANSITION	NOMINAL PULL-OUT STRENGTH	PACKAGING	SHIP WEIGHT (lbs)
1-402723	1.00" Shur-Lock II SDR to Hybrid 1.295"-1.335" to 1.330"-1.370"	600 lbs	10/CTN	4
1-402711	1.00" Shur-Lock II SG/FC to SDR 1.400"-1.440" to 1.295"-1.335"	600 lbs	10/CTN	4
1-402725	1.00" Shur-Lock II SG/FC to Hybrid 1.400"-1.440" to 1.330"-1.370"	600 lbs	10/CTN	4
1-400762	1.25" Shur-Lock II SG/FC to Hybrid 1.640"-1.680" to 1.570"-1.610"	700 lbs	10/CTN	5
1-406976	4.00" Shur-Lock II SDR to 4.00" SDR 13.5 4.480"-4.520" to 4.637"-4.677"	1,000 lbs	4/CTN	15

Center stop is removed to allow the coupler to be pulled back over the end of the duct for limited clearance installations.

PART #	SHUR-LOCK II COUPLER NO STOP (NS)	NOMINAL PULL-OUT STRENGTH	PACKAGING	SHIP WEIGHT (lbs)
20002340	1.00" Shur-Lock II Coupler SDR 1.315" ± 0.020" 	600 lbs	10/CTN	5
20000236	1.25" Shur-Lock II Coupler SDR 1.660" ± 0.020" 	700 lbs	10/CTN	6
20002341	1.50" Shur-Lock II Coupler SDR 1.900" ± 0.020" 	800 lbs	10/CTN	6
20002374	1.50" Shur-Lock II Coupler-Extended SDR 1.900" + 0.020"  (8.75" long vs 5.75" standard)	800 lbs	10/CTN	6
20000237	2.00" Shur-Lock II Coupler SDR 2.375" ± 0.020" 	800 lbs	10/CTN	7
20000251	2.00" Shur-Lock II Coupler-Extended SDR 2.375" ± 0.020"  (8.25" long vs 5.75" standard)	800 lbs	10/CTN	8
20000238	2.50" Shur-Lock II Coupler SDR 2.875" ± 0.020" 	1,000 lbs	6/CTN	8
20000239	3.00" Shur-Lock II Coupler SDR 3.500" ± 0.020" 	1,000 lbs	6/CTN	11
20000260	4.00" Shur-Lock II Coupler SDR 4.500" ± 0.020" 	1,000 lbs	4/CTN	15
20001531	5.00" Shur-Lock II Coupler SDR 5.563" ± 0.020" 	1,000 lbs	2/CTN	18
20000261	6.00" Shur-Lock II Coupler SDR 6.625" ± 0.020" 	1,000 lbs	2/CTN	20

PART #	SHUR-LOCK II COUPLER BELL ADAPTER	NOMINAL PULL-OUT STRENGTH	PACKAGING	SHIP WEIGHT (lbs)
20002439	1.25" Adapter, Bell SL-BE 125-135	1,000 lbs	10/CTN	7
20002376	2.00" Adapter, Bell SL-BE 020-135	1,000 lbs	10/CTN	20
20001486	3.00" Adapter, Bell SL-BE 030-135	1,000 lbs	4/CTN	20
20001465	4.00" Adapter, Bell SL-BE 040-135	1,000 lbs	4/CTN	20
20000270	5.00" Adapter, Bell SL-BE 050-135	1,000 lbs	4/CTN	20
20000271	6.00" Adapter, Bell SL-BE 060-135	1,000 lbs	4/CTN	20



 Please specify if ETL listing is required.



Spreads open the ends of the no-stop couplers to facilitate installation on to the duct end.

PART #	SHUR-LOCK II NO STOP (NS) SPREADER TOOL	PACKAGING	SHIP WEIGHT (lbs)
1-905906	1.00" Shur-Lock II Spreader	EACH	1
1-905907	1.25" Shur-Lock II Spreader	EACH	1
1-905908	1.50" Shur-Lock II Spreader	EACH	2
1-905909	2.00" Shur-Lock II Spreader	EACH	2
1-905910	2.50" Shur-Lock II Spreader	EACH	3
1-905911	3.00" Shur-Lock II Spreader	EACH	3
1-906163	4.00" Shur-Lock II Spreader	EACH	4
1-906164	5.00" Shur-Lock II Spreader	EACH	5
1-906165	6.00" Shur-Lock II Spreader	EACH	6



PART #	PALM RATCHET	PACKAGING	SHIP WEIGHT (lbs)
20002747	Palm Ratchet with 5/16" and 7/16" Sockets. Used with Shur-Lock II and Split-Lock couplers.	EACH	1

 Please specify if ETL listing is required.