



GROUND ROD CLAMPS

SRC Universal Ground Rod Clamp

- Bronze alloy or stainless steel hardware both UL listed and approved for direct burial in earth and concrete.
- Performs the functions of economy, standard duty, heavy duty, and extra heavy duty.
- Able to withstand torque in excess of UL 467 requirements of 150 in/lb.
- RUS listed.



One Clamp Fits 1/2, 5/8 and 3/4 Rod Diameters.

Catalog Number	Rod Size	Conductor Range	Master Pack	Wt. Per 100	NAED UPC No. 632591-
SRC	1/2"	1/0 Str. - 10 Sol.	100	16	613286
SRC	5/8"	1/0 Str. - 10 Sol.	100	16	613286
SRC	3/4"	1/0 Str. - 10 Sol.	100	16	613286

Notes: Listed for galvanized and copper ground rods
 UL Listed for US and Canada
 This clamp accommodates all 1/2, 5/8 and 3/4-inch ground rods

SRC-SS Stainless Steel Universal Ground Rod Clamp

- Made from 304 stainless steel.
- UL-Listed and marked for copper coated, galvanized, and stainless steel ground rods; also for #4, #5 and #6 (1/2", 5/8" and 3/4") rebar.
- UL-Listed in US and Canada for direct burial in earth and concrete.
- One size fits all.
- Patent pending.
- Made In USA.



One Clamp Fits 3/8, 1/2, 5/8 and 3/4 Rod Diameters.

Catalog Number	Rod Size	Conductor Range	Master Pack	Wt. Per 100	NAED UPC No. 632591-
SRC-SS	3/8"	1/0 Str. - 10 Sol.	100	9	61499-3
SRC-SS	1/2"	1/0 Str. - 10 Sol.	100	9	61499-3
SRC-SS	5/8"	1/0 Str. - 10 Sol.	100	9	61499-3
SRC-SS	3/4"	1/0 Str. - 8 Sol.	100	9	61499-3

Notes: When used with stainless steel ground rods, the wire range is #8 solid to #2 stranded.