

Heritage Plastics created the long bell for ease and efficiency. In compliance with the industry standards, Heritage Plastics PVC Electrical Conduit is manufactured from virgin PVC compounds complying with the UL651 standards as described in the standards specifications for rigid PVC compounds ASTM D 1784-81. Our PVC Electrical Conduits are subject to in-process quality control to assure compliance with appropriate manufacturing and performance standards.

- UL 651
- RUS Listed
- NEMA TC-2
- NEMA TC-3 (Accessories)
- UL Standard 514 B (Accessories)
- General Service Administration (GSA) WC 1094A
- National Electric Code - Article 352
- Sunlight and Weather resistant
- Reduced emissions of smoke & HCL
- Listed for 90° C conductors or cable and direct sunlight
- Rigid nonmetallic raceway for wires and cables in accordance with the NEC
- Superior weathering characteristics

Schedule 40 Electrical Conduit

10' Part #	20' Part #	Nominal Size	Weight 100'	Pack Qty 10'	O.D.	I.D.	Wall
510510	510520	1/2"	16.4	6,000'	.840	.622	.109
510710	510720	3/4"	21.8	4,400'	1.050	.824	.113
511010	511020	1"	32.1	3,600'	1.315	1.049	.133
511310	511320	1 1/4"	43.4	3,300'	1.660	1.380	.140
511510	511520	1 1/2"	51.8	2,250'	1.900	1.610	.145
512010	512020	2"	69.5	1,400'	2.375	2.067	.154
512510	512520	2 1/2"	109.6	930'	2.875	2.469	.203
513010	513020	3"	143.5	880'	3.500	3.068	.216
513510	513520	3 1/2"	169.1	630'	4.000	3.548	.226
514010	514020	4"	204.3	570'	4.500	4.026	.237
515010	515020	5"	277.6	380'	5.563	5.047	.258
516010	516020	6"	360.0	260'	6.625	6.065	.280

