



ERITECH® Copper-bonded Ground Rods

In a grounding system, the ground electrode provides the physical connection to the earth and is the instrument used to dissipate current into it. There are two main types of electrodes.

"Natural" electrodes are intrinsic to the facility and include metal underground water pipe, the metal frame of the building (if effectively grounded), and reinforcing bar in concrete foundations.

"Made" electrodes are installed specifically to improve the performance of the grounding system and include wire meshes, metallic plates, buried copper conductor and rods or pipe driven into the ground.

The ground rod is the most widely used grounding electrode. ERICO offers a complete line of rods and accessories to meet the industry needs.



Features

Copper-bonded Ground Rods

- Resist corrosion better than galvanized rods allowing for approximately 30-year service life in most soils
- State of the art manufacturing process helps ensure uniform plating thickness
- Minimum tensile strength of 80,000 psi and straightness tolerance of .010" per linear foot
- Exceed the requirements of ANSI®/UL® 467, CSA, and ANSI/NEMA® GR-1

Pointed Copper-bonded Ground Rods

- Manufactured of high strength 1018 cold drawn steel
- The ERICO preferred ground rod

Compression Couplers for Pointed Rods

- For use when coupling pointed rods

Sectional Copper-bonded Ground Rods

- For use when it is necessary to deep-drive rods
- Cold-rolled threads - stronger than cut threads

Threaded Couplers for Sectional Rods

- For use when coupling sectional rods

Drive Studs for Sectional Rods

- Screws into threaded coupler while rod is being driven


Applications

ERICO has a complete line of ground rods and accessories to meet the industry needs.

More Information

View product information by region: [North & Latin America](#) · [Europe](#) · [Asia & Australia](#)

Product Information - North & Latin America [Return to Top](#)

<input type="checkbox"/> ERITECH Pointed Copperbonded Ground Rod	<input type="checkbox"/> ERITECH Copperbonded Sectional Ground Rod		<input type="checkbox"/>	<input type="checkbox"/>
--	--	---	--------------------------	--------------------------

Pointed Ground Rod	Sectional Ground Rod	Compression Coupler for Pointed Rods	Threaded Coupler for Sectional Rods	Drive Stud for Sectional Rods
--------------------	----------------------	--------------------------------------	-------------------------------------	-------------------------------

Pointed Copper-bonded Ground Rods

Part No.	Plating Thickness (mil)	Diameter (in)	Length (ft)	Standard Package	Weight per 100
613880	10	3/8	8	5	270
611380*	10	1/2	8	5	553
611300*	10	1/2	10	5	738
615850	10	5/8	5	5	420
615860	10	5/8	6	5	509
615880*	10	5/8	8	5	680
615883*	13-REA	5/8	8	5	680
615800*	10	5/8	10	5	844
615803*	13-REA	5/8	10	5	844
615812*	10	5/8	12	5	1000
615815*	10	5/8	15	5	1275
613460	10	3/4	6	5	750
613480*	10	3/4	8	5	1000
613483*	13	3/4	8	5	1000
613400*	10	3/4	10	5	1240
613412*	10	3/4	12	5	1480
613415*	10	3/4	15	5	1850
614400*	10	1	10	5	2204

* UL Listed

Sectional Copper-bonded Ground Rods

Part No.	Plating Thickness (mil)	Diameter (in)	Length (ft)	Standard Package	Weight per 100
631380*	10	FS 1/2	8	5	540
631300*	10	FS 1/2	10	5	688
635830	10	5/8	3	5	262
635840	10	5/8	4	5	344
635850	10	5/8	5	5	420
635860	10	5/8	6	5	504
635880*	10	5/8	8	5	680
635883*	13- REA	5/8	8	5	680
635800*	10	5/8	10	5	844

633480*	10	3/4	8	5	1000
633400*	10	3/4	10	5	1240
634400*	10	1	10	5	2204

* UL Listed

Product Information - Europe[Return to Top](#)

Part Number	Description	Nominal Diameter		Length		Pack	Unit Weight (kg)
		mm	inches	m	feet		
155000	1.2M38*	9	3/8"	1.2	4	5	0.650
155010	1.5M38*	9	3/8"	1.5	5	5	0.800
155030	2.1M38*	9	3/8"	2.1	7	5	1.100
155050	3.0M38*	9	3/8"	3.0	10	5	1.600
155060	1.2M12	12.5	1/2"	1.2	4	5	0.800
155070	1.5M12	12.5	1/2"	1.5	5	5	1.150
155090	2.1M12	12.5	1/2"	2.1	7	5	1.600
155110	3.0M12	12.5	1/2"	3.0	10	5	2.300
155240	1.2M58	14.2	5/8"	1.2	4	5	1.500
155250	1.5M58	14.2	5/8"	1.5	5	5	1.900
155270	2.1M58	14.2	5/8"	2.1	7	5	2.450
155290	3.0M58	14.2	5/8"	3.0	10	5	3.750
155420	1.2M34	17.2	3/4"	1.2	4	5	2.150
155430	1.5M34	17.2	3/4"	1.5	5	5	2.750
155450	2.1M34	17.2	3/4"	2.1	7	5	3.800
155470	3.0M34	17.2	3/4"	3	10	5	5.450

* Non-Extending

ANSI is a registered trademark of the American National Standards Institute. NEMA is a registered service mark of National Electrical Manufacturers Association. UL is a registered trademark of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

WARRANTY

ERICO products are warranted to be free from defects in material and workmanship at the time of shipment. NO OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), SHALL EXIST IN CONNECTION WITH THE SALE OR USE OF ANY ERICO PRODUCTS. Claims for errors, shortages, defects or nonconformities ascertainable upon inspection must be made in writing within 5 days after Buyer's receipt of products. All other claims must be made in writing to ERICO within 6 months from the date of shipment or transport. Products claimed to be nonconforming or defective must, upon ERICO's prior written approval in accordance with its standard terms and procedures governing returns, promptly be returned to ERICO for inspection. Claims not made as provided above and within the applicable time period will be barred. ERICO shall in no event be responsible if the products have not been stored or used in accordance with its specifications and recommended procedures. ERICO will, at its option, either repair or replace nonconforming or defective products for which it is responsible or return the purchase price to the Buyer. THE FOREGOING STATES BUYER'S EXCLUSIVE REMEDY FOR ANY BREACH OF ERICO WARRANTY AND FOR ANY CLAIM, WHETHER SOUNDING IN CONTRACT, TORT OR NEGLIGENCE, FOR LOSS OR INJURY CAUSED BY THE SALE OR USE OF ANY PRODUCT.

LIMITATION OF LIABILITY

ERICO excludes all liability except such liability that is directly attributable to the willful or gross negligence of ERICO's employees. Should ERICO be held liable its liability shall in no event exceed the total purchase price under the contract. ERICO SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS OF BUSINESS OR PROFITS, DOWNTIME OR DELAY, LABOR, REPAIR OR MATERIAL COSTS OR ANY SIMILAR OR DISSIMILAR CONSEQUENTIAL LOSS OR DAMAGE INCURRED BY BUYER.

Due to a policy of continued product development, specifications are subject to change without notice.

Copyright © 2013 ERICO International Corporation.
CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

