

619 - ASPHALTIC PATCHING (SPECIFIED DEPTH)/PARTIAL DEPTH PATCHING

619.1 DESCRIPTION

The Contractor will be responsible for asphalt crack repairs as shown on the plans. Asphalt Patching shall apply to existing asphalt pavements. Partial Depth Patching shall apply to asphalt patching on existing concrete pavements.

619.2 CONSTRUCTION REQUIREMENTS

The pavement shall be removed to the depth as shown on the plans and disposed by the contractor. Asphaltic Concrete Intermediate Course shall be placed at the depth shown on the plans. All asphalt patching (specified depth)/partial depth patching repairs shall be removed and replaced the same day. All asphalt patching (specified depth)/partial depth patching repairs shall be completed prior to the overlay.

619.3 MEASUREMENT AND PAYMENT

The Engineer will measure asphaltic patching by the ton. Traffic control, sawing, milling and removal for asphalt patching, asphalt, compaction, and replacement of asphaltic concrete are all subsidiary to "Asphalt Patching".

The Engineer will measure partial depth patching by the square foot. Traffic control, sawing, milling and removal for partial depth patching, asphalt, compaction, and replacement of asphaltic concrete are all subsidiary to "Partial Depth Patching".

Payment for "Asphalt Patching" and "Partial Depth Patching" at the contract unit price bid is full compensation for the specified work.