



-NOTES-

1. FINISH: HOT DIP GALVANIZE PER ASTM-A153 (LATEST REVISION).
2. BASEPLATE TO BE PERPENDICULAR TO SHAFT AXIS ($\pm 1^\circ$) AND HOLE CENTERLINE CONCENTRIC ($\pm .188$) TO SHAFT AXIS.
3. STENCIL MIN. 1/2" IN. LETTERS MANUFACTURER'S NUMBER AFTER GALVANIZING.
4. PILOT POINT AND SHAFT AXES TO BE CONCENTRIC ($\pm .125$ FIM) AND IN LINE ($\pm 2^\circ$)
5. FLAME CUT TWO SLOTS IN SHAFT PERPENDICULAR TO THE BASEPLATE.
6. PREHEAT, TUMBLEBLAST, HANDDRIND, AND CLEAN BASEPLATE, HELIX, AND PILOT POINT ON ALL WELDED AREAS.
7. FLAMECUT IRREGULARITIES PERMISSIBLE: (1) VALLEYS NOT TO EXCEED 3/32" BELOW NOMINAL SURFACE LEVEL, (2) PEAKS OR POSITIVE IRREGULARITIES NOT TO EXCEED 1/32" IN. ABOVE NOMINAL SURFACE LEVEL OR INTERSECTIONS OF NOMINAL SURFACES.
8. MANUFACTURER TO HAVE IN EFFECT INDUSTRY RECOGNIZED WRITTEN QUALITY CONTROL FOR ALL MATERIALS AND MANUFACTURING PROCESSES.
9. ALL MATERIAL IS TO BE NEW, UNUSED AND MILL TRACEABLE MEETING THE FOLLOWING SPECIFICATIONS:
 BASEPLATE: ASTM A36-(LATEST REVISION) STRUCTURAL STEEL
 (CONFORM TO AASHTO TECH. BUL. #270)
 SHAFT: ASTM A252-(LATEST REVISION) GRADE 2, STEEL PIPE PILES.
 ALTERNATE MATERIAL: ASTM A53-(LATEST REVISION) TYPE E OR S, GRADE B, STEEL PIPE OR ASTM A500-(LATEST REVISION) GRADE B, STRUCTURAL STEEL TUBING.
 HELIX: ASTM A635-(LATEST REVISION) 3/8" THICK HOT ROLLED STEEL PLATE OR COIL.
 PILOT POINT: ASTM A575-(LATEST REVISION) 1-1/4" DIAMETER HOT ROLLED STEEL BAR.
 BOLTS: HEX HEAD BOLT, 1.0-8UNC-2A PER ANSI B-18.5, SAE J429 GRADE-5.
 ANTI-THEFT BOLTS: STAINLESS HEX HEAD MACHINE BOLTS, 1/4-20-UNC2A PER ASTM A276.
 NUTS: HEAVY HEX NUTS PER ASTM A194 GRADE 2H OR ASTM A563 GRADE DH, MEETING THE SUPPLEMENTARY REQUIREMENTS OF ASTM A563, 1-8UNC-2B PER ANSI B18.2.2.
 ANTI-THEFT CLAMP ASSEMBLY: STEEL PER ASTM A36 STRUCTURAL STEEL.
 RUBBER PADS: ELASTOMER PER CLASS 4 RUBBER BLANKET. MINIMUM DF 40 DURDROMETER.
 BASEPLATE IS PERMANENTLY STAMPED WITH MANUFACTURER'S IDENTIFICATION 'ABC' IN 1/2" LETTERS AND DATE CODE IN 1/4" LETTERS.
 BASEPLATE PERMANENTLY MARKED TO INDICATE CABLEWAY OPENING IN SHAFT.

LIGHTING FOUNDATION
 CAT. NO. T1120363-ATKC

<p>CHANCE</p>			
<p>CONCEPTUAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, REPRODUCTION, OR TRANSMISSION OF ANY INFORMATION WRITTEN OR DRAWING HEREON IS PERMITTED WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS UNPUBLISHED. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</p>		<p>HUBBELL POWER SYSTEMS</p>	
<p>TITLE</p>		<p>LIGHTING FOUNDATION</p>	
<p>SIZE</p>	<p>DWG NO.</p>	<p>DWN BY</p>	<p>DATE</p>
<p>SB</p>	<p>SA1120363-ATKC</p>	<p>JWH</p>	<p>11/14/14</p>
<p>DO NOT SCALE THIS DRAWING</p>	<p>SHEET 1/1</p>	<p>REV</p>	<p>--</p>