



Split Conduit

For enclosing fiber optics and cables, installing conduit around existing cable, or repairing sections of damaged conduit.

Our Split Conduit is an innovative and efficient PVC product that is great for enclosing fiber optics, cables, and repairing damaged conduit.

When snapped together, the unique interlocking design of Split Conduit creates a smooth tight seal protecting the cable or fiber optics from weathering. No tape, plastic, or metallic straps are needed to seal or provide extra strength to the Split Conduit.

Manufactured from a UL listed PVC compound specifically designed for power and communications applications, our Split Conduit displays superior impact strength and ultraviolet resistance

* The ETL listing does not apply to our Type C and 1 inch Sch. 40 products.

** 1 ¼ inch, 2 inch, and 2.5 inch split conduit is also available in CPVC plastic. [Contact us for more information.](#)



SCH 40 SPLIT CONDUIT

PART NUMBER	DESCRIPTION	I.D.	O.D.	WEIGHT PER 10 FT.	MINIMUM ORDER
P1F	1" SPLIT-DUCT CONDUIT	1.049	1.315	4.5 lbs.	10 ft.




1-800-670-1804

+1-435-673-1804

[Get a Quote](#)[Request Catalog](#)

HOME	COMPANY	PRODUCT DEMO			FAQ	CONTACT
P2F	2" SPLIT-DUCT CONDUIT	2.007	2.375	8.0 lbs.	10 ft.	
P25F	2.5" SPLIT-DUCT CONDUIT	2.469	2.875	12.0 lbs.	10 ft.	
P3F	3" SPLIT-DUCT CONDUIT	3.068	3.500	16.0 lbs.	10 ft.	
P4F	4" SPLIT-DUCT CONDUIT	4.026	4.500	22.0 lbs.	10 ft.	
P5F	5" SPLIT-DUCT CONDUIT	5.047	5.563	29.0 lbs.	10 ft.	
P6F	6" SPLIT-DUCT CONDUIT	6.065	6.625	39.5 lbs.	10 ft.	

SCHEDULE 80 SPLIT CONDUIT

PART NUMBER	DESCRIPTION	I.D.	O.D.	WEIGHT PER 10 FT.	MINIMUM ORDER
P2F80	2" SCH. 80 SPLIT-DUCT CONDUIT	1.939	2.375	11.0 lbs.	10 ft.
P4F80	4" SCH. 80 SPLIT-DUCT CONDUIT	3.746	4.500	30.0 lbs.	10 ft.

TYPE C SPLIT CONDUIT

PART NUMBER	DESCRIPTION	I.D.	O.D.	WEIGHT PER 10 FT.	MINIMUM ORDER
PCD4F	4" SPLIT C DUCT	4.060	4.350	14.0 lbs.	10 ft.